

FEATURES:

- Input: AC 100-240V~ 50/60Hz
- AC INLET: C8 or C6 or C14
- Power: 180-200W series
- Ovp, ocp, scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 179*85*40mm
- Application: Consumer electronics, Telecom and office equipment



SAFETY:

| SAFETY: | |
|-----------------|--|
| Safety Standard | UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335 |
| Safety Approval | UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV |
| EMC Standard | EMC EMISSION: EN55035 class B (CISPR32), EN61000-3-2,-3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2,3,4,5,6,8,11, EN55024; light industry level, criteria A, EAC TP TC 020 |
| MTBF | 50K hrs min. MIL-HDBK-217F (25°C) |

MODEL LIST:

180W DESKTOP ADAPTERS SERIES

| MODEL | INPUT VOLTAGE | POWER | OUTPUT VOLTAGE | OUTPUT CURRENT | INLET TYPE |
|----------------|---------------|-------|----------------|----------------|-------------|
| SW-1201500-S20 | 100-240VAC | 180W | 12V | 15.0A | C8, C6, C14 |
| SW-1501200-S20 | 100-240VAC | 180W | 15V | 12.0A | C8, C6, C14 |
| SW-2400750-S20 | 100-240VAC | 180W | 24V | 7.5A | C8, C6, C14 |
| SW-3600500-S20 | 100-240VAC | 180W | 36V | 5.0A | C8, C6, C14 |
| SW-4800375-S20 | 100-240VAC | 180W | 48V | 3.75A | C8, C6, C14 |

200W DESKTOP ADAPTERS SERIES

| MODEL | INPUT VOLTAGE | POWER | OUTPUT VOLTAGE | OUTPUT CURRENT | INLET TYPE |
|----------------|---------------|-------|----------------|----------------|-------------|
| SW-1501200-S20 | 100-240VAC | 180W | 15V | 12.0A | C8, C6, C14 |
| SW-2001000-S20 | 100-240VAC | 200W | 20V | 10.0A | C8, C6, C14 |
| SW-2400830-S12 | 100-240VAC | 200W | 24V | 8.3A | C8, C6, C14 |
| SW-3600500-S12 | 100-240VAC | 200W | 36V | 5.0A | C8, C6, C14 |
| SW-4800416-S12 | 100-240VAC | 200W | 48V | 4.16A | C8, C6, C14 |

Mechanical Diagram:

