

FEATURES:

- Input: AC 100-240V~ 50/60Hz
- Available plug: US, EU plug
- Power: 5W 1A , 5V 1.2A series
- Ovp, ocp, scp and Over load protection
- Ripple < 120mV
- Efficiency level: VI
- Dimension: 47.7*34.4*23.3mm(exclude plug)
- Application: Consumer electronics, Telecom and office equipment



SAFETY:

SAFETY:	
Safety Standard	UL 62368, IEC 62368, EN 61558, IEC60601, IEC60335
Safety Approval	UL/cUL, CE, FCC, UKCA, PSE, CB, SAA, KC, TUV
EMC Standard	EMC EMISSION: EN55032 class B (CISPR32), EN61000-3-2, -3, EAC TP TC 020 EMC IMMUNITY: EN61000-4-2, 3, 4, 5, 6, 8, 11, EN55024; light industry level, criteria A, EAC TP TC 020
MTBF	50K hrs min. MIL-HDBK-217F (25°C)

MODEL LIST:

5W WALL MOUNTED SERIES

MODEL	INPUT VOLTAGE	POWER	OUTPUT VOLTAGE	OUTPUT CURRENT	PLUG TYPE
SW-01050100-S04z	100-240VAC	5W	5V	1.0A	US, EU
SW-01050120-S04z	100-240VAC	6W	5V	1.2A	US, EU

Mechanical Diagram

